

JAC
FORKLIFT

MATERIAL HANDLING EXPERTS
FROM AUTOMOTIVE QUALITY

CPD10-15S

Electric Mini Three-wheel Forklift






JAC HEAVY DUTY IMPORT & EXPORT CO.,LTD

SPECIFICATIONS

Model	Unit	CPD10S	CPD13S	CPD15S
Power		Battery	Battery	Battery
Manner of operation		Seated	Seated	Seated
Load capacity	kg	1000	1300	1500
The max. lifting height(mm)	kg	700	900	1000
Service Weight(kg)	kg	1840	2050	2190
Load center distance(mm)	mm	500	500	500
Distance between fork backrest and front wheel	mm	235	235	170
Wheel base	mm	1090	1090	1090
Tires		Polyurethane / solid rubber	Polyurethane / solid rubber	Polyurethane / solid rubber
Front Wheel size,number		Φ 305×127、 2	Φ 305×127、 2	Φ 305×127、 2
Driving Wheel size,number		Φ 250×127、 1	Φ 250×127、 1	Φ 250×127、 1
The width between front wheels	mm	783	783	783
Lifting height	mm	3000	3000	3000
Free lifting height	mm	135	135	135
Lowered mast height	mm	1995	1995	1995
Extended mast height	mm	3949	3949	3949
Mast/Fork carriage tilt forward/backward	°	2/5	2/5	2/5
Overhead load guard (cab) height	mm	1980	1980	1980
Seat height	mm	960	960	960
Overall length	mm	2530	2530	2465
Overall width	mm	917	917	917
Fork size, Thickness/Width/Length	mm	35/100/950	35/100/950	35/100/950
Fork adjust width	mm	220-750	220-750	220-606
Ground clearance under mast	mm	90	90	90
Ground clearance, center of wheelbase	mm	90	90	90
Aisle width for pallets 1000×1200 cross ways	mm	2930	2930	2865
Aisle width for pallets 800×1200 length ways	mm	3038	3038	2975
Turning radius	mm	1348	1348	1348
Max.gradient performance, laden/unladen	%	6/10	6/10	6/10
The max driving speed laden/unladen	km/h	6.2/7.2	6.2/7.2	6.2/7.2
Lift speed,laden/unladen	mm/s	135/215	135/215	135/215
Lowering speed,laden/unladen	mm/s	238/225	238/225	238/225
Driving Motor	V/kw	24V/2.5kw	24V/2.5kw	24V/2.5kw
Lifting Motor	V/kw	24V/4.5kw	24V/4.5kw	24V/4.5kw
Steering Motor	V/kw	24V/0.2kw	24/0.2kw	24V/0.2kw
Battery voltage	V/Ah	24V/300Ah	24V/350Ah	24V/400Ah
Working time of fully charged batteries (h)	h	5	5	5
Battery dimensions	mm	645/292/500	645/292/535	645/292/570

The company reserves the right to change the parameters without notice.

LOAD CAPACITY



ADDRESS: SHANGHAI ROAD, BAOHE INDUSTRIAL PARK, HEFEI, ANHUI, CHINA PC. 230051

TEL: 86-551-62297986

FAX: 86-551-62297990

WEB: www.jaczg.com ; www.jacforklift.com

E-mail: jac@jaczg.com

All Rights Reserved by JAC heavy duty co.,ltd. Parameter updating without notice, the picture just for reference. 2021/05/28